



TECHNICAL DATA SHEET

PRODUCT LINE dryMIX TOT

It is a fine, loose type II admixture (without co-combustion materials) for the production of concrete, precast concrete and building components.



Possible uses:

- Admixture to improve hydration properties in concrete products



TECHNICAL DATA SHEET

The following standards apply to the product:

- ČSN EN 450-1 Fly ash for concrete. Part 1: Definitions, specifications and conformity criteria
- ČSN EN 450-2 Fly ash for concrete. Part 2: Conformity assessment

Basic characteristic data:

 1023 Teplárna Otrokovice a.s., Objízdná 1777, 765 02 07 1023-CPR-1094-P EN 450-1	
Fly ash for concrete TOTPLAST admixture type II (without co-incinerated materials)	
Fineness	category N
Declared fineness value	30 %
Loss on annealing	category A
Specific gravity	(2400 ± 200) kg/m ³

Our services:

- active support in project acquisition
- design and optimization of the recipe according to the contractor's specifications
- production control tests, samples taken directly on site "in situ"
- rental of mobile construction sites
- comprehensive service, logistics
- cooperation with accredited testing laboratories

Delivery form:

- The DM TOT product is transported in bulk in tanker trucks of approximately 27 tons and is pumped into silos directly on site. The condition is always a passable road for tanker trucks!
- Take advantage of our technical experience gained on specific construction sites by using these products!
- We are happy to optimize our products with regard to your construction requirements.

We look forward to working with you!